

Zitrec[®] EC 10

Waterbased OAT technology

Zitrec[®] EC 10 is a ready to use water based heat transfer fluid customised for datacenters and other electronic applications. Developed specifically for high-demand applications, this heat transfer fluid incorporates patented organic inhibitors, ensuring long-lasting corrosion protection for the entire system.

In an era where datacenters are adapting to higher CPU¹ and GPU² Thermal Design Power with lower case temperatures driven by new technologies like AI³ and ML⁴, traditional air-cooling methods often prove inadequate. Water based liquid cooling addresses this challenge by offering superior thermal management, significantly improving Power Usage Effectiveness (PUE) and reducing cooling energy consumption, which typically accounts for 80% of a data center's non-IT energy usage.

With Zitrec[®] EC 10, datacenter operators can confidently meet the escalating cooling demands of modern technology, ensuring efficient, safe and environmentally responsible operations.



PRODUCT BENEFITS



Optimal thermal performance

- **Zitrec[®] EC 10** offers superior thermal performance ideal for overclocking and similar applications using solely water as base fluid.



Protecting critical surfaces

- Carefully balanced organic inhibitors prevent scaling and offer exceptional corrosion resistance, safeguarding critical metal surfaces like copper, aluminium, (stainless) steel and brass throughout their lifespan;
- High compatibility with various elastomers and thermoplastics, ensuring integrity and performance of system components.



Reduced maintenance

- Depletion free and stable inhibitor package;
- Bacteriostatic.



Environment and safety

- Carefully selected formula to minimise environmental impact;
- Nitrite, borate and 2-EHA free technology;
- The non-hazardous nature of the product ensures safety during handling and usage;
- Expected to be readily biodegradable

1 CPU: Central Processing Unit
 2 GPU: Graphical Processing Unit
 3 AI: Artificial Intelligence
 4 ML: Machine Learning

Application

Arteco's **Zitrec® EC 10** is designed as a liquid heat transfer medium for a wide range of applications and particularly recommended for high demanding power electronic components which do not need boil and freeze protection. Some examples where **Zitrec® EC 10** is suitable for: **liquid cooled Direct-to-Chip applications, HPC (High Performance Compute), Overclocking and Datacom Equipment Center Cooling.**



Power Electronics



Edge Computing



Servers



High Performance Computing

Toxicity & safety

For toxicity information, safe handling and disposal of the product, we refer to the Safety Data Sheet. This product should not be used to protect the inside of drinking water systems against freezing.

Packaging

Arteco's **Zitrec® EC 10** is available in the following packs & colours:



IBC 1000L



Colour options upon request

Contact details

Should you have questions with regards to Arteco's **Zitrec® EC 10**, related to available packages or colours or on one of the other Arteco solutions, please do not hesitate to contact your local Area Sales Manager or send your inquiry to info@artecco-coolants.com.

Addendum - Technical information

Chemical and Physical Properties

Property	Zitrec® EC 10	Unit	Method	OCP requirements	ASHREA requirements
Appearance	Clear liquid		visual		
Nitrite, amine, phosphate, borate, silicate	-				
Specific gravity (20°C)	1.003 typ.	kg/l	ASTM D5931		
Refractive Index (20°C)	1.337 typ.		ASTM 1218		
pH (20°C)	8.5 typ.		ASTM D1287	8.0 - 10.5	8.0 - 9.5
Turbidity	1	NTU		< 5	< 20
Total Harness as CaCO ₃	0	ppm		< 2	< 0
Chloride	2	2		< 50	< 5
Microbiological control - bacteria	0	cfu/ml		<1	<100

Engineering data

Temperature	Density (kg/m ³)	Specific Heat (kJ/kg.K)	Thermal Conductivity (W/mK)	Dynamic Viscosity (cP = mPa.s)	Kinematic Viscosity (cSt = mm ² /s)
10°C	1004	4.18	0.570	1.5	1.5
20°C	1003	4.17	0.586	1.2	1.2
30°C	1000	4.17	0.601	0.9	0.9
40°C	996	4.17	0.615	0.7	0.7
50°C	992	4.17	0.627	0.6	0.6
60°C	987	4.17	0.638	0.5	0.5
70°C	981	4.17	0.647	0.4	0.5

ASTM D1384 - Glassware corrosion test

	Weight loss in mg/coupon ¹					
	Brass	Copper	Solder	Steel	Cast Iron	Aluminium
Specification	10	10	30	10	10	30
Zitrec® EC 10	2	1	1	0	-1	7

¹ Weight loss AFTER chemical cleaning according to ASTM procedure. Weight gain is indicated by a - sign

Shelflife & storage requirements

Zitrec® EC 10 can be stored for minimum 2 years in unopened recipient without any effect on the product quality or performance. It is strongly recommended to use new non-translucent containers and where possible packages with a UV filter. Direct sunlight and high temperatures can degrade the quality of the product. **Zitrec® EC 10** should be stored above 0°C and below 35°C. Periods of exposure to temperatures above 35°C should be minimised.

Zitrec® EC 10 is not compatible with galvanized steel.

Compatibility and mixability

For optimal performance:

- Artec's **Zitrec® EC 10** is compatible with most other heat transfer media based on water, propylene glycol or ethylene glycol. Exclusive use is however recommended for optimum corrosion protection and sludge control.

The information contained in this Product Information Leaflet is intended to provide the customer and/or end-user with an understanding of the properties of the product, it being understood that this information may not be construed as any express or implied warranty that the product is suitable for a specific use or application. All information contained in this Product Information Leaflet, including but not limited to text or graphic material, is the property of Artec NV, is accurate to the best of our knowledge at the date of issue specified, supersedes all previous editions and information contained in them, and is subject to change without notice. Any textual or graphic material you copy, print, or download from this Product Information Leaflet is for your personal, non-commercial use only, and you not change or delete any copyright, trademark or other proprietary notices. Any other use, including but not limited to the reproduction, distribution, display or transmission of the content of this document is strictly prohibited, unless authorized by Artec NV in writing.

Version 202501-v01.1